

AG 系列

靜音型集中粉碎機

Sound-Proof Central Granulator



恩普
ANYPAS

特點 Features

- ★ FG系列, (功率5HP~100HP) 適用於電子、汽車、化工和吹塑成型系統
FG Series (motor power 5HP~100HP) designed for crushing electron, chemical, blow molding parts or bottles.
- ★ 進料口大, 大件廢料易粉碎。可移動。清料容易, 換網快 Large feed opening for ease of feeding. Easy maintenance, easy to clean and easy to move.
- ★ 可選用多種尺寸過濾篩網, 調整粉碎顆粒大小 High performance perforated screen in various sizes
- ★ 馬達過載保護、緊急安全開關裝置 Motor overload protection and emergency stop button.
- ★ 選購配備旋風器, 可有效分離粉塵 選購配備送料風車,
- ★ 可自動送料, 提高效率 Option of cyclone suction unit for extraction of regrinds. Option of regrind conveying system.

規格表 Specification

機 型 Model	AG30 Series			AG45 Series					AG55 Series				
	AG3020	AG3025	AGL3030	AG4530	AG4540	AG4550	AG4560	AG4570	AG5555	AG5570	AG5585	AG55100	
馬 達(HP) Motor power	5	7.5	10	15	20	25	30	40	40~50	50~60	60~70	70~100	
送風機功率(kw) Fan power	0.75~1.5KW			1.1~2.2KW					3~4				
轉 速 (rpm) Rotating speed	680			680					680				
刀片類型 Blade type	Paddle blade			Paddle blad					Paddle blade				
固定刀片數量 (Nos) Fixed blade	2	2	2	2	2	2	4	4	4	4	4	4	
轉動刀片數量 Rotating blade (Nos)	3	3	3	3	3	3	6	6	6	6	6	6	
粉碎入口尺寸 (mm) Feed opening	300*200	300*250	300*300	450*300	450*400	450*500	450*600	450*700	550*550	550*700	550*850	550*1000	
最大粉碎能力(kg/hr) Max. output	60~100	70~120	80~150	150~250	200~300	250~350	300~400	350~450	400~600	500~700	600~800	700~1000	
粉碎時噪音 Db(A) Noise level	78~82			85					85				
外形尺寸 Dimensions	L (mm)	610	610	710	1000	1100	1210	1310	1410	1690	1840	1990	2140
	W (mm)	1000	1000	1000	1200	1200	1400	1400	1400	1750	1750	1800	1800
	H (mm)	1700	1700	1700	1320	990	1850	1850	1850	2500	2500	2800	2800
重量 (KG) Weight	550	650	800	1000	1200	1400	1600	1800	1800	3400	4200	5000	